

Natural Deck Oil™ - Directions for Use

PREPARATION: Prepare wood with appropriate BIO-WASH® product. Apply STAIN PREP™ and then rinse with plenty of water. Let wood dry for at least two to three hours or until dry-to-touch. Apply finish within 12 hours of applying STAIN PREP™. STAIN PREP™ is a pH balancing cleaner that increases coating penetration and maximizes coating life.

APPLICATION: Stir NATURAL DECK OIL™ well prior to use. Apply a small test area to ensure desired colour. Apply out of direct sunlight and on a cool surface above 40 F (5 C). If the surface is above 100 F (38 C) do not apply product. "The Hand Touch Test™" is when the wood feels hot to touch. Apply at least two coats of NATURAL DECK OIL™ with a nylon/polyester paintbrush. Wait about two hours or until first coat is dry-to-touch to apply next coat. If spraying, saturate a small surface at a time and then immediately back-brush to promote saturation of the wood.

DRY TIME: NATURAL DECK OIL™ will be dry to touch in one to two hours. A complete cure of the coating for walked on surfaces is 48 hours at 65°F (12°C) and 50% humidity. Avoid application of product when the daily low is below 40°F (5°C) or rain is in the immediate forecast.

CLEAN UP: Clean up tools immediately with water. Overspray and spills are easily cleaned with tap water before coating dries. If overspray and spills have dried use STRIPEX® -L to remove NATURAL DECK OIL™.

MAINTENANCE: A maintenance coating is required if rain water immediately penetrates into wood. Prepare wood with STAIN PREP™ MILL GLAZE AWAY within 12 hours prior to applying a maintenance coat of NATURAL DECK OIL™. After protecting your wood with NATURAL DECK OIL™ use SIMPLE WASH™ to keep it clean.

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Keep product from freezing.

SAFETY CONCERNS: NATURAL DECK OIL™ is the safest clear wood coating available. It is non-flammable, has a low odour, is water-based and its application has no effects on the environment.

WARRANTY: The manufacturers and distributors liability under any expressed or implied guarantee/warranty is limited solely to replacement of products shown defective. Claims must be made within one year of purchase and be accompanied by proof of purchase. The manufacturers and distributors shall not be liable for injury, cost of labour, or direct, incidental or consequential damages.

COVERAGE GUIDE- Use 2 coats

	First Coat	Second Coat
Smooth Wood	19 sq. m. per 3.8 litre	28 sq. m. per 3.8 litre
Rough Wood	14 sq. m. per 3.8 litre	23 sq. m. per 3.8 litre

If wood is very wet, coating penetration will be lower and coverage will be reduced.

Allow wood to "dry to touch" for best coverage and protection.