



## WOOD OILS - Ingredient Data

August 1998

Full declaration of ingredients

### **Binding agents:**

- based on the re-growing vegetable raw materials sunflower oil, soybean oil and thistle oil.

### **Solvents:**

- aliphatic hydrocarbons = disaromatized white spirit (benzolefree, in compliance with purity demands of DAB 10 ff, German Pharmacopoeia, 10th edition ff).

### **Earths:**

- mineral origin, silicic acid and swelling clays.

The used mineral pigments and earths have been purified from all poisonous ingredients (e. g. heavy metals) and are physiologically safe.

### **Additives:**

- zinc-zirconium-cobalt-octoates (are obtained from the respective minerals and are leadfree)

-ketoximes

- polysiloxanes (on the basis of silicic acid)

The listed ingredients serve to a regular drying and the prevention of film formation (5 years storage stability) as well as a strong water repellency.

According to EG requirements OC COLOR WOOD OIL does not have to be marked and will not emit physiologically harmful compounds to environment.

OS COLOR WOOD OIL does not contain biocides nor preservatives. The dried finish is safe for man, animal and plant, and is in compliance with the German industrial Norm DIN 53160 (fast to perspiration and saliva) and Euro Norm 71 (safety of children's toys). Test certificates are available.

Further details concerning technical characteristics etc, can be obtained from the respective product information.