

GRADE & QUALITY DESCRIPTION

Silva A & Better Clear

GRADING CRITERIA Western Red Cedar (*Thuja plicata*) Battens

General Notes

Graded to BS1186-3 Part 4 Class 1.
High-quality production - exceeds NLGA grading rules
Clean, consistent almost entirely knot free appearance
Green (not kiln dried)
PEFC Certified.

Wood Fibre

Fine grained, old growth wood from forests in coastal regions of British Columbia, Canada.

Knots

Permitted

Occasional small sound tight knots are allowed within the official industry grading rules*. Most pieces are entirely free of knots, other than occasional pin knots.

Sap Wood

Permitted

Occasional light sapwood may be present on a small percentage of boards.

Compression Wood

Permitted

Occasional – unlikely to be present.

Deformation (Warp)

Permitted

Boards with minor curvature and twisting, as far as proper installation is ensured. As a guide, a 10mm deviation from true is permitted on a 19 x 38 x 2440mm board. The longer the board, the greater the deviation from true is permitted.

www.silvatimber.co.uk | enquiries@silvatimber.co.uk | 0151 495 3111 | 020 8150 8055



Registered Office: Unit 4 Albright Road, Widnes, Cheshire, WA8 8FY
Registered in England and Wales No: 4626406
VAT Registration Number: 756 3271 21

WE DISCOVER
YOU CREATE



Checks

Permitted

Small checks permitted.

Splits

Permitted

Short splits permitted in a small percentage of boards.

Torn or Raised Grain

Permitted

Light torn or raised grain permitted.

Machining / Handling Marks

Permitted

Occasional minor marks / blemishes / stains may be present.

Colour Variation

Permitted

Colour can vary between boards and within boards.

Typical colour range: light straw to dark reddish brown.

Notes

- Silva offers this information as a general guide to the main characteristics likely to be encountered in any shipment of Silva Clear A & Better Clear material.
- Since no two pieces of timber are identical, complete uniformity throughout a shipment is impossible.
- Grading is not an exact science because it is based on a visual inspection of each piece and the grader's judgment.
- Most boards will be fully usable; however, the installer will be required to trim some boards to remove undesirable defects.
- Other minor wood characteristics not listed may occasionally be present but would not detract from the material's usability.
- On occasion, knot sizes and other characteristics may fall outside of the typical sizes quoted.

**National Lumber Grades Authority (NLGA) Standard Grading Rules for Canadian Lumber - paragraph 200b.*

www.silvatimber.co.uk | enquiries@silvatimber.co.uk | 0151 495 3111 | 020 8150 8055



Registered Office: Unit 4 Albright Road, Widnes, Cheshire, WA8 8FY
Registered in England and Wales No: 4626406
VAT Registration Number: 756 3271 21