



RESPECT FOR HUMANS

WINKLER cares about the world surrounding us. You are the main beneficiary of our products.



RESPECT FOR ENVIRONMENT

The contemporary world is overloaded with toxic products hardly disposable. Our health and the health of our children is affected everyday by this.



SAFE STORAGE

Advanced research made this product safe and compliant with fire and transportation regulations; Safety and tranquility of our clients is our mission.



CONTINUOUS RESEARCH

Our R&D laboratory always keeps updated the competence on raw materials, working to understand all the necessity related to the product.

TECHNICAL CHARACTERISTICS

| | |
|---|---------------------------------------|
| PRODUCT APPEARANCE | Colorless to straw yellow liquid |
| APPLIED PRODUCT COLOR | Trasparent |
| PRODUCT STATE | Liquid |
| V.O.C. (g/l) | 0 |
| WATER VAPOR TRANSMISSION CONCRETE (ASTM D 6490) | 0.71 WVT (grains/h ft2) 1.74 Perms |

Would you like to see how to use SKERMO TERRAZZE in the best way? Scan with your smartphone the QR code for further information.



Manufactured by Winkler Srl
Via M.Buonarroti, 15 - 20093 Cologno Monzese Milano - Italy
Tel. +39 02 26 700 605 - Fax +39 02 26 700 621 | info@winklerchimica.com - www.winklerchimica.com
Imported in United States by Winkler USA - 88 S. State Street, Hackensack, NJ 07601
1 (201) 488-9291 - info@winklerusa.com



SKERMO TERRAZZE

Transparent penetrating sealer for tiled balconies and terraces





**PROTECTING HUMANS
WHILE REMAINING
FRIENDLY
TO THE ENVIRONMENT**

Products that carry
WINKLER SAFE Technology



help increase safety
of the user on the job site.

**W-Safe products are solvent free
and have very low environmental
impact, thus reducing pollution
and increasing the quality
of life and work.**

**As a result of the most advanced
research in the industry,
W-Safe Technology innovation
stands equally for low
environmental impact
and for utmost quality
and the excellent technical
characteristics of the products
that carry this logo.**

SKERMO TERRAZZE

Transparent penetrating sealer
for tiled balconies and terraces

The constant research of WINKLER R&D Laboratories in nanotechnology made possible the formulation of SKERMO TERRAZZE, a penetrating sealer of excellent quality and efficacy in the treatment of balconies and terraces with water infiltration problems.

NATURE OF THE PRODUCT

SKERMO TERRAZZE, is an innovative product of latest generation, solvent free with 100% active material, specifically developed to waterproof balconies and terraces subjected to water infiltration. Once applied, the product stops the water infiltration by penetrating deep into the substrate and thus ensuring an exceptional durability for at least 10 years.

CHARACTERISTICS

SKERMO TERRAZZE, is non-pellicular and does not change the breathability and the color of the treated surfaces. Its waterproofing action prevent the formation of efflorescence, musk, mold, lichens bacterium, etc. which represent a serious problem for balconies, terraces and for the well being of buildings. It protects the treated surfaces from ageing and from degradation due to freeze-thaw cycles. Its special formulation stops the penetration of chlorides and therefore it is strongly suggested for marine areas. Surfaces treated with SKERMO TERRAZZE have a better protection against dust, soot and from pollution in general.

FIELD OF USE

SKERMO TERRAZZE is a penetrating sealer that provides long lasting protection against water infiltration to balcony (terrace) floors covered with ceramic tiles, clinker, terracotta tile, concrete, etc.



SURFACE PREPARATION AND APPLICATION

Clean all support surfaces thoroughly in order to eliminate dirt, dust, and loose or crumbling parts, any other foreign substances. Remove any eventual stains on the tiles using a neutral detergent. Apply WINGROUT FLEX to treat eventual cracked or otherwise damaged grouting. The product application needs to be done either on dry or damp surface (not on a wet surface).

Apply SKERMO TERRAZZE with roller or brush on the entire tiled surface, paying close attention to properly "soak to saturation" the grout area. After 15 minutes, remove eventual excess using a clean cloth. Protect from walking and water in any form for minimum of 18 hours from the application.



WARNINGS

Before applying the product on a full scale, perform a mock-up test on a small, less visible portion of the support in order to check the chromatic stability. Apply the product in conditions that allow the fastest penetration at temperatures between +5°C and +35°C or 41°F and 95°F (ambient and substrate). So do not apply on frozen surfaces, inclement weather (present or upcoming) nor under direct sun exposure.

CONSUMPTION

Over tiled surfaces: 15 m²/l or 150 Sq. ft. per Qt.

PACKAGING

1 L (1.05 Qt.) bottle.
5 L (5.25 Qt.) pail.

STORAGE

Store for 18 months in its undamaged, unopened package in a shaded and protected place at temperature between +5°C and +35°C or 41°F and 95°F. Not frost-proof.

