



LUP is a light duty joist hanger for supporting timber joists from timber members.



[UK-DoP-e06/0270](#), [ETA-06/0270](#)

FEATURES



Material

- Pre-galvanised mild steel.



APPLICATIONS

Suitable On


- For supporting solid timber joists from timber members.

When to Use

- Solid sawn timber connections.

TECHNICAL DATA

Product Dimensions



References	Joist Size [mm]				Product Dimensions [mm]							Header holes	Joist holes
	Width		Height		A	B	C	D	F	t	Ø5 [mm]	Ø5 [mm]	
	Min	Max.	Min	Max.									
LUP230/38	36	38	100	150	38	96	38	23	38	1	6	-	
LUP230/44	42	44	100	150	44	93	38	23	38	1	6	-	
LUP230/47	45	47	100	150	47	92	38	23	38	1	6	-	
LUP230/50	48	50	100	150	50	90	38	23	38	1	6	-	

Product Capacities

References	Characteristic capacities - Timber to timber - Full nailing				
	Number of Fasteners			Product characteristic capacities - Timber C24 [kN]	Safe Working Loads [kN]
	Header	Joist		R _{1,k}	R _{1,SWL,Long term}
	Qty	Qty	Qty - Speed prongs	N3.75x30	C24 header N3.75x30
LUP230/38	6	-	2	4	2.9
LUP230/44	6	-	2	4	2.9
LUP230/47	6	-	2	4	2.9
LUP230/50	6	-	2	4	2.9

INSTALLATION



Speed prongs
fix the hanger
into position
ready for
nailing.