



Western Red Cedar Certi-split Shakes Coverage Guide

Approximate nails usage guide - 1 kilo of 2.65 x 50mm Stainless Steel Annular Ringshank Nails will be required to fix 4 bundles of Premium shakes / 3 bundles of #2 Grade shakes

Recommended use (Premium) - A premium option for a wide range of uses, particularly main building roofs and walls where rustic character is desired.

Recommended use (#2 Grade) - An economical option offering great deal of versatility. Contain a high proportion of high quality tiles.

Batten spacing - Space battens to coincide with the weather exposure. Spacing between adjacent shingles (joints) should be a minimum of 6mm and a maximum of 9mm. Joints in any one course should be separated not less than 38mm from joints in adjacent courses and in any three courses, no two joints should be in direct alignment.

Coverage (approximate)	#2 Grade Tapersawn	Premium Tapersawn	Premium Handsplit
1 Bundle on roofs with a 13°+ pitch	1.38m ²	1.80m ²	1.80m ²

Recommended Exposure

	Fivex (406mm)	Perfection (457mm)	Royal (610mm)
Roofs with a 19° > pitch	114mm	254mm	190mm
Roofs with a pitch 14 - 19°	102mm	/	190mm

Shingle Specification

	Fivex (406mm)	Perfection (457mm)	Royal (610mm)
Shingle Length	450mm	610mm	610mm
Maximum Shingle Width	76mm	100mm	100mm
Shingle Butt Thickness	15-19mm	16mm	16mm

Bundle Specification (approximate)			
Bundle Length	635mm	440mm	410mm
Bundle Width	482mm	656mm	650mm
Bundle Height	228mm	141mm	260mm