



ENVIRO STAIN®

WOOD LIGHTENER

DESCRIPTION Brightens all wood surfaces, particularly wood treated with Sansin Wood Cleaner™. Treated surfaces often appear darker than expected and Wood-Lightener will restore the original natural color of the wood.

APPLICATIONS

Used to neutralize and restore wood surfaces treated with Sansin Wood-Cleaner™.

PRODUCT BENEFITS

- Biodegradable
 - Made in Canada
 - Interior and Exterior
 - Low VOC
 - Non flammable
-

CHARACTERISTICS

- Coloring.....
 - Appearance.....
 - Odor.....
 - Form.....
 - Specific Gravity (g/cm³).....
 - Density (lbs/gall).....
 - pH,.....
 - Viscosity, @Zahn 4 @21°C.....
 - Solvents.....
 - Freezing Point.....
 - Diluent.....
 - Cleanup.....
 - Drying Time (To touch) @ 20°C (68°F)Do not allow to dry
 - Coverage (Depending on coating appearance and thickness) 150-300 sqft
 - Shelf lifeLooses strength slowly over time
 - VOC(g/l).....
-

PACKAGING

Available in 1 gallon bag

PREPARATION

- Substrate must be dry above 10°C (50°F).
- Spray vegetation with water or shield off before and after application

- Protect all border areas with drop sheets and/or tape off with poly all areas not being cleaned
 - Do not allow this product to contact metal, fabric, floor coverings or outdoor furniture
 - Keep children and pets away from work area while using Wood-Lightener™
-

APPLICATION METHODS

- Dissolve Wood-Lightener in 1.5 – 2.0 gal (5.75 – 7.5L) of water depending on the amount of brightening you require.
 - Always ensure a liberal and uniform application.
 - Apply using a brush, roller or spray to a dry wood surface
 - On vertical surfaces start at bottom and work up
 - Allow Wood-Lightener to work 5-15 minutes to revive the natural wood color.
 - Do not allow Wood-Lightener™ to dry
 - Do not apply in direct sunlight
 - Thoroughly rinse with water using a garden hose or pressure washer (maximum pressure 500 PSI)
 - Ensure thorough rinse as a slight residue can affect the coating performance.
 - Allow wood to completely dry
-

WORKING PROCEDURE

- Do not allow to dry as this will require reapplication
- Do not apply in direct sunlight
- Allow the product to work 5-15 minutes
- Thoroughly rinse the surface using a garden hose or low pressure power washer (max pressure 500psi)
- Direct the power washer wand with the grain of the wood
- Don not stop the wand on the wood as this may mark the wood surface
- Allow the wood to dry completely

STORAGE

- Close and seal package
- Store in cool dry
- Avoid exposure to sunlight
- Do not allow freezing
- Rinse container thoroughly before disposal according to regulations

SAFETY Caution: Eye Irritant. Contains Citric Acid. If splashed in eyes, rinse eyes with water for 20 minutes. Consult physician. See Material Safety Data Sheet

WARNING TO USERS

Wear protective gear during application: ie rubber gloves, rubber pants, rubber coat, rubber boots goggles, and a NIOSH/MSHA approved respirator when spraying. Project

surfaces become extremely slippery when working. Avoid walking on surface while wet. Keep out of reach of children, if swallowed immediately drink two glasses of orange juice.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

September 2009