



Certigrade No. 1 Grade (Blue Label) Yellow Cedar Shingles Coverage Guide

Approximate nails usage guide - 1 kilo of 1.8 x 31mm Stainless Steel Annular Ringshank Flat Head Nails will be required to fix 4 bundles of shingles.

Recommended use - The premium grade for many applications where a good quality finish is required.

Batten spacing - Space battens to coincide with the weather exposure. Spacing between adjacent shingles (joints) should be a minimum of 6mm and a maximum of 9mm. Joints in any one course should be separated not less than 38mm from joints in adjacent courses and in any three courses, no two joints should be in direct alignment.

Coverage (approximate)	Square Metres
1 Bundle on roofs with a 19°+ pitch	2.32m ²
1 Bundle on roofs with a pitch 14 - 19°	1.76m ²
1 Bundle on vertical sidewalls	3.45m ²

Recommended Exposure

Shingle Length	(mm)
Roofs with a 19° > pitch	125mm
Roofs with a pitch 14 - 19°	95mm
Vertical sidewalls (single course)	175mm
Vertical sidewalls (double course)	300mm

Shingle Specification

Shingle Length	
Shingle Width	405mm
Minimum Shingle Width	75mm (minus tolerance of 65mm in 10% bundle)
Maximum Shingle Width	355mm

Shingle Butt Thickness	10mm (5butts together = 50mm)
Grading	Clear heartwood; 100% edge grain; no defects

Bundle Specification (approximate)	
Bundle Length	635mm
Bundle Width	482mm
Bundle Height	228mm
Bundle Weight	15-35kg (depending on moisture content)